

**WL231 4G MIFI Spec**

<b>Model</b>	WL231	
<b>Description</b>	4G Power bank Mifi	
<b>Product Dimension</b>	TBD	
<b>Body</b>	<b>size</b>	<b>99*60*31mm</b>
	<b>weight</b>	<b>220g</b>
<b>Protocol</b>	LTE TDD/FDD	3GPP R9 Cat. 4, Downlink/Uplink up to 150Mbps/50Mbps
	WCDMA	3GPP R7 Downlink/Uplink up to 21Mbps/5.76Mbps
<b>RF BAND</b>	FDD LTE	1/ 3 /5 /7/8/20/28 (其它频段可选定制)
	TDD-LTE	38/40/41
	WCDMA	1/5/8
<b>WIFI Protocol</b>	IEEE 802.11n	Support
	IEEE 802.11g	Support
	IEEE 802.11b	Support
<b>Frequency</b>	2.4G	1~13 channel
<b>Antenna</b>	Internal Antenna connector	LTE Main*1/Diversity antenna*1 WIFI antenna*1
<b>External Interface</b>	SIM card slot	Micro SIM card
	Power interface	Standard USB Type C*1, USB Type A*1
	Power button	Support
	Reset button	Support
<b>Indicator</b>	LED indicator	WIFI/Connection *1, Power display*4
<b>Power Supply</b>	USB output	5V/2.4A
	USB input	5V/2.4A
<b>Battery</b>	Lithium polymer	10000mAh
<b>Software</b>		
	<b>Standard WEB UI</b>	

<b>WEB UI</b>	Quick Setup	support
	Dashboard (Device Status)	support
	Internet Settings	support
	Home Network Settings	support
	Wireless Settings	support
	Router Settings	support
	System Settings	support
	SMS	support
	Phonebook	Support
<b>System upgrade</b>	Firmware upgrade	support(via FOTA/PC upgrade) FOTA server is required from the customer
<b>Operation System</b>	WIN7(32bit/64bit)、WIN8,WIN10,Mac OS X10.6 and above version	
<b>Environment</b>	Working Temperature	0~45℃
	Storage Temperature	-20~70℃
<b>Cettification</b>	CE	TBD
	RoHS	TBD